MS510

Digital Projector

2,700 ANSI Lumens | 4000:1 | SVGA | 2W Speaker | DLP 3D READY

HIGHLIGHTS

- -2700 ANSI Lumen
- -SVGA Auflösung
- -erweiterte Lampen-Lebensdauer
- -Quick Cooling
- -Standby Verbrauch < 1W
- -3D Ready
- -BrilliantColor™
- -3D Color Managment
- -Keystone ±40°
- -2W Speaker
- -Quick Auto Search
- -Passwortschutz
- -HDTV Kompatibel

Projections System	DLP® technology by Texas Instruments®	
Native Auflösung	SVGA (800 x 600)	
Helligkeit	2700 ANSI lumens	
Kontrast	4000:1 (Full on/Full off)	
Keystone	Manual Vertical ±40°	
Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Linse	F= 2.51 to 2.69, f= 21.95 ~ 24.18 mm	
Zoom Ratio	Manual Zoom, 1.10:1	
Bilddiagonale min./max.	23" to 300"	
Throw Ratio	1.97-2.17 (50"@ 2m)	
Lampe	190W, 4500/6000 hours (Normal/Economic mode)	
Computer Kompatibilität	VGA(640 x 480) to UXGA(1600 x 1200)	
HDTV Kompatibilität	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Kompatibilität	NTSC, PAL, SECAM	
Horizontale Frequenz	31-82 kHz	
Verticale Scan Rate	48-85 Hz	
Eingänge	PC	Analog RGB: D-sub 15 pin x 2
	A/V	HDMI V1.3 x 1
		Component Video: D-sub 15 pin x 2
		(Shared with Analog RGB connector)
		S-Video: Mini Din 4 pin x 1
		Composite Video: RCA x 1
	Audio	Stereo Mini Jack x 1
Ausgänge	PC	Monitor Out: D-sub 15 pin x 1
	Audio	Variable Audio Out : Stereo Mini Jack x 1
		Speaker: 2W x 1
Steuerungs-Schnittstellen	Serial Connector : RS232 9 pin x 1	
	USB Connector : USB Type B x 1	
Maaße (B x H x T)	265 x 100 x 210 mm r(10.4 x 3.9 x 8.3 inch)	
Gewicht	2.3 kg (5.1 lbs)	
Stromversorgung	100 to 240 VAC, 50/60 Hz	
Leistungsaufnahme	250W, Standby < 1W	
Lautstärke	30/28 dB (Normal/Economic mode)	
On-Screen Display Sprachen	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Indonesia/ Italian/ Janpanese/ Kroean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages)	
Bildmodis	Dynamic Mode	Presentation Mode
	sRGB Mode	Cinema Mode
	User 1 Mode	User 2 Mode
Besondere Funktionen	BrilliantColor™	Quick Auto Search
	Closed Captioning	Wall Color Correction
	Teaching Template	3D Ready
	3D Color Management	Blank
	Digital Zoom (x2)	Auto Off
	Freeze	Security Password
	HDTV compatible	"Q?" Hot Key for FAQ
	High Altitude Mode	Auto Adjustment Hot Key
Zubehör (Standard)	Quick Start Guide	VGA Cable
	Manual CD	Power Cord
	Remote Control w/battery	
Zubehör (Optional)	Presentation Plus	Spare Lamp Kit
	RS232 Cable	Soft Carry Case